

GUILLOTINE **IDEAL 4810-95**

POWER GUILLOTINE WITH MANUAL SPINDLE CLAMPING SYSTEM

475 mm cutting length | electro-mechanical blade drive | manual spindle clamp, guided on both sides, with large hand wheel | spindle guided backgauge with hand crank | measuring scale (mm/inches), located on front table | adjustable backgauge with narrow separations and plastic gliders | two side lays each on front and rear tables | high-quality blade made from "Solingen steel" | solid steel blade carrier and adjustable blade guides | solid all-metal construction | complete with stand and storage shelf | SCS (Safety Cutting System): hinged, electronically controlled safety guard on the front table; transparent safety cover on the rear table; main switch and safety lock with key; electronically controlled true two-hand operation; 24 volt controls (low voltage); patented IDEAL safety drive; automatic blade return from every position; disc brake for instant blade stop; blade changing device with covered cutting edge; blade depth adjustment from the outside of the machine; easy blade change from the front of the machine without removing covers.

Power supply: 230 V / 50 Hz / 1~¹, Motor performance (input capacity): 1.1 kW

Dimensions (H x W x D): 1360 x 755 x 970 mm, Weight: 194 kg, Colour: pearl grey.

¹ other voltages available



SAFETY GUARD




The electronically secured front safety guard swings out of the way easily and allows safe and convenient cutting.

SIDE LAY



Two side lays on the front table and the precise backgauge allow exact positioning even for small paper stock.

MEASURING SCALE



The precise measuring scale (mm/inches) for the backgauge positioning can be read easily and is located on the front table.

IDEAL 4810-95

Cutting length	475 mm
Cutting height	80 mm
Narrow cut	30 mm
Table depth	458 mm
Power supply	230 V / 50 Hz ¹